

## REMARKS


The present Preliminary Amendment is submitted to delete the multiple dependencies of claims 3, 5-6, 10-12, 14-15, 22-24, 33, 37, and 39 thereby placing such claims in condition for examination and reducing the required PTO filing fee.

Copies of the amended portion of the claims with changes marked therein is attached and entitled "*Version with Markings to Show Changes Made.*"

Respectfully submitted,

Shinji OKUDA et al.

By



Michael S. Huppert  
Registration No. 40,268  
Attorney for Applicants

MSH/kjf  
Washington, D.C. 20006-1021  
Telephone (202) 721-8200  
Facsimile (202) 721-8250  
May 9, 2001

CLAIMS

1. A bead molding method for molding a hollow bead from a highly viscous material that is fluid in the form of a stream in a high speed flow region and can retain a shape into which it is molded in a low speed flow region; comprising:

a gas stream forming step for forming a gas stream in a one direction;

a material stream forming step for forming a highly viscous material stream flowing in the high speed flow region within an outer peripheral space about and enclosing the gas stream; and

a bead molding step for molding the hollow bead into an irregular shape by reducing the flow speed of the highly viscous material stream from the high speed flow to the low speed flow while rendering the highly viscous material stream fluid within the outer peripheral space about and enclosing the gas stream.

2. A bead molding method for molding a hollow bead from a foamable material for forming a foamed body, comprising:

a gas stream forming step for forming a gas stream in a one direction;

a material stream forming step for forming a foamable material stream flowing in the same direction as the gas stream within an outer peripheral space about and enclosing the gas stream; and

a bead molding step for molding the hollow bead into an irregular shape by reducing the flow speed of the

foamable material stream from the high speed flow to the low speed flow while fluidizing the foamable material stream flowing within the outer peripheral space about and enclosing the gas stream.

3. The bead molding method as claimed in claim 1 or 2, wherein the bead molding step molds the hollow bead into a shapes corresponding to and following the shape of the applying position by applying the work with the hollow bead or the foamable material onto the applying position while transferring the streams along the applying position.

4. The bead molding method as claimed in claim 3, wherein the hollow bead applied and molded are tackied or adhesived to the work by using the highly viscous material or the foamable material has an tackinessly or adhesive property.

5. The bead molding method as claimed in ~~any one of~~ claims 1 to 4, further comprising a discharging device including an inner nozzle elongated at a tip portion thereof and an outer nozzle elongated about and enclosing an outer periphery of the inner nozzle; wherein:

the gas stream forming step forms the gas stream in the one direction by discharging gases from the inner nozzle; and

the material stream forming step forms the highly viscous material stream or the foamable material stream in the same direction of the gas stream about and enclosing the gas stream by discharging the highly viscous material or the foamable material from the outer nozzle.

6. The bead molding method as claimed in claim 3 [or 4], wherein there is disposed a discharging device including an inner nozzle elongated at a tip portion thereof and an outer nozzle elongated about and enclosing an outer periphery of the inner nozzle;

the gas stream forming step forms the gas stream in the one direction by discharging the gases from the inner nozzle;

the material stream forming step forms a stream of the highly viscous material or the foamable material in the same direction of the gas stream about and enclosing the gas stream by discharging the highly viscous material or the foamable material from the outer nozzle; and

the bead molding step molds a hollow bead into a shape corresponding to and following the shape of the applying position by discharging the highly viscous material stream or the foamable material stream toward the work from the inner nozzle and the outer nozzle in the outer ~~peripheral~~<sup>peripheral</sup> space of the gas stream while transferring the nozzles in a locus corresponding to and following the shape of the applying position.

7. A bead molding method for molding a foamed bead into a given shape, composed of a foamed body covered with a highly viscous material that is fluid in the form of a stream in a high speed flow region and retains the shape into which it is molded in a low speed flow region, comprising:

a foamable material stream forming step for forming a

stream of a foamable material for forming the foamed body in a one direction;

a material stream forming step for forming a stream of the highly viscous material in the high speed flow region in an outer peripheral space enclosing and about the foamable material stream; and

a foamed bead molding step for molding the foamed bead into an irregular shape by foaming the foamable material while fluidizing the highly viscous material flowing in the outer peripheral space of the foamable material stream and reducing the high speed flow of the foamable material stream to the low speed flow thereof.

8. The bead molding method as claimed in claim 7, wherein the foamed bead molding step molds the foamed bead into the given shape by following the shape of the applying position while transferring the foamable material stream and the highly viscous material stream along the shape of the applying position while applying the work with the foamable material and the highly viscous material.

9. The bead molding method as claimed in claim 8, wherein the highly viscous material has an tackinessly or adhesive property and the foamed bead applied and molded are tackied or adhesived to the work.

10. The bead molding method as claimed in ~~any one of~~ claims 7 [to 9] wherein:

there is disposed a discharging device including an inner nozzle elongated at its tip and an outer nozzle elongated about and enclosing an outer periphery of the

[illegible]

27  
 28  
 29  
 30  
 31  
 32  
 33  
 34  
 35  
 36  
 37  
 38  
 39  
 40  
 41  
 42  
 43  
 44  
 45  
 46  
 47  
 48  
 49  
 50  
 51  
 52  
 53  
 54  
 55  
 56  
 57  
 58  
 59  
 60  
 61  
 62  
 63  
 64  
 65  
 66  
 67  
 68  
 69  
 70  
 71  
 72  
 73  
 74  
 75  
 76  
 77  
 78  
 79  
 80  
 81  
 82  
 83  
 84  
 85  
 86  
 87  
 88  
 89  
 90  
 91  
 92  
 93  
 94  
 95  
 96  
 97  
 98  
 99  
 100

[illegible]

27  
 28  
 29  
 30  
 31  
 32  
 33  
 34  
 35  
 36  
 37  
 38  
 39  
 40  
 41  
 42  
 43  
 44  
 45  
 46  
 47  
 48  
 49  
 50  
 51  
 52  
 53  
 54  
 55  
 56  
 57  
 58  
 59  
 60  
 61  
 62  
 63  
 64  
 65  
 66  
 67  
 68  
 69  
 70  
 71  
 72  
 73  
 74  
 75  
 76  
 77  
 78  
 79  
 80  
 81  
 82  
 83  
 84  
 85  
 86  
 87  
 88  
 89  
 90  
 91  
 92  
 93  
 94  
 95  
 96  
 97  
 98  
 99  
 100

[illegible]

27  
 28  
 29  
 30  
 31  
 32  
 33  
 34  
 35  
 36  
 37  
 38  
 39  
 40  
 41  
 42  
 43  
 44  
 45  
 46  
 47  
 48  
 49  
 50  
 51  
 52  
 53  
 54  
 55  
 56  
 57  
 58  
 59  
 60  
 61  
 62  
 63  
 64  
 65  
 66  
 67  
 68  
 69  
 70  
 71  
 72  
 73  
 74  
 75  
 76  
 77  
 78  
 79  
 80  
 81  
 82  
 83  
 84  
 85  
 86  
 87  
 88  
 89  
 90  
 91  
 92  
 93  
 94  
 95  
 96  
 97  
 98  
 99  
 100  
 101  
 102  
 103  
 104  
 105  
 106  
 107  
 108  
 109  
 110  
 111  
 112  
 113  
 114  
 115  
 116  
 117  
 118  
 119  
 120  
 121  
 122  
 123  
 124  
 125  
 126  
 127  
 128  
 129  
 130  
 131  
 132  
 133  
 134  
 135  
 136  
 137  
 138  
 139  
 140  
 141  
 142  
 143  
 144  
 145  
 146  
 147  
 148  
 149  
 150  
 151  
 152  
 153  
 154  
 155  
 156  
 157  
 158  
 159  
 160  
 161  
 162  
 163  
 164  
 165  
 166  
 167  
 168  
 169  
 170  
 171  
 172  
 173  
 174  
 175  
 176  
 177  
 178  
 179  
 180  
 181  
 182  
 183  
 184  
 185  
 186  
 187  
 188  
 189  
 190  
 191  
 192  
 193  
 194  
 195  
 196  
 197  
 198  
 199  
 200  
 201  
 202  
 203  
 204  
 205  
 206  
 207  
 208  
 209  
 210  
 211  
 212  
 213  
 214  
 215  
 216  
 217  
 218  
 219  
 220  
 221  
 222  
 223  
 224  
 225  
 226  
 227  
 228  
 229  
 230  
 231  
 232  
 233  
 234  
 235  
 236  
 237  
 238  
 239  
 240  
 241  
 242  
 243  
 244  
 245  
 246  
 247  
 248  
 249  
 250  
 251  
 252  
 253  
 254  
 255  
 256  
 257  
 258  
 259  
 260  
 261  
 262  
 263  
 264  
 265  
 266  
 267  
 268  
 269  
 270  
 271  
 272  
 273  
 274  
 275  
 276  
 277  
 278  
 279  
 280  
 281  
 282  
 283  
 284  
 285  
 286  
 287  
 288  
 289  
 290  
 291  
 292  
 293  
 294  
 295  
 296  
 297  
 298  
 299  
 300  
 301  
 302  
 303  
 304  
 305  
 306  
 307  
 308  
 309  
 310  
 311  
 312  
 313  
 314  
 315  
 316  
 317  
 318  
 319  
 320  
 321  
 322  
 323  
 324  
 325  
 326  
 327  
 328  
 329  
 330  
 331  
 332  
 333  
 334  
 335  
 336  
 337  
 338  
 339  
 340  
 341  
 342  
 343  
 344  
 345  
 346  
 347  
 348  
 349  
 350  
 351  
 352  
 353  
 354  
 355  
 356  
 357  
 358  
 359  
 360  
 361  
 362  
 363  
 364  
 365  
 366  
 367  
 368  
 369  
 370  
 371  
 372  
 373  
 374  
 375  
 376  
 377  
 378  
 379  
 380  
 381  
 382  
 383  
 384  
 385  
 386  
 387  
 388  
 389  
 390  
 391  
 392  
 393  
 394  
 395  
 396  
 397  
 398  
 399  
 400  
 401  
 402  
 403  
 404  
 405  
 406  
 407  
 408  
 409  
 410  
 411  
 412  
 413  
 414  
 415  
 416  
 417  
 418  
 419  
 420  
 421  
 422  
 423  
 424  
 425  
 426  
 427  
 428  
 429  
 430  
 431  
 432  
 433  
 434  
 435  
 436  
 437  
 438  
 439  
 440  
 441  
 442  
 443  
 444  
 445  
 446  
 447  
 448  
 449  
 450  
 451  
 452  
 453  
 454  
 455  
 456  
 457  
 458  
 459  
 460  
 461  
 462  
 463  
 464  
 465  
 466  
 467  
 468  
 469  
 470  
 471  
 472  
 473  
 474  
 475  
 476  
 477  
 478  
 479  
 480  
 481  
 482  
 483  
 484  
 485  
 486  
 487  
 488  
 489  
 490  
 491  
 492  
 493  
 494  
 495  
 496  
 497  
 498  
 499  
 500  
 501  
 502  
 503  
 504  
 505  
 506  
 507  
 508  
 509  
 510  
 511  
 512  
 513  
 514  
 515  
 516  
 517  
 518  
 519  
 520  
 521  
 522  
 523  
 524  
 525  
 526  
 527  
 528  
 529  
 530  
 531  
 532  
 533  
 534  
 535  
 536  
 537  
 538  
 539  
 540  
 541  
 542  
 543  
 544  
 545  
 546  
 547

[illegible][illegible]

discharging the foamable material stream and the highly viscous material stream onto the applying position from the inner nozzle and the outer nozzle, respectively.

12. The bead molding method as claimed in claim 6 [or 11], wherein:

the discharging device is mounted on a manipulator disposed to be transferable to a desired position in response to a control signal; and

the bead molding step for applying and molding the hollow bead or the foamed bead automatically on the applying position of a plurality of work members being carried one after another on a manufacturing line by controlling a movement of the discharging device by means of the manipulator.

13. The bead molding method as claimed in claim 12, wherein an actual applying position of the bead applied by the discharging device is detected and the manipulator is controlled so as to substantially bring the actual applying position thereof into agreement with a predetermined target applying position.

14. The bead molding method as claimed in claim 12 [or 13], wherein it is decided to automatically determine whether the bead is applied and molded in a favorable fashion by desired picking up an image of the bead applied and molded on the applying position and comparing the picked-up image of the bead with a reference image of a bead applied and molded in a predetermined favorable fashion.

15. The bead molding method as claimed in ~~any one of~~

claims/ 12 [to 14], wherein the work member comprises an opening and closing member for closing a predetermined opening thereof.

16. The bead molding method as claimed in claim 15, wherein the applying position comprises a site disposed along and nearby an edge portion of the opening and closing member, and the hollow bead or the foamed bead applied and molded on the applying position forms a sealing section that seals a gap between the opening and the opening and closing member.

17. A bead molding apparatus for molding a hollow bead comprising:

a discharging device including an inner nozzle disposed extending at a tip portion, an outer nozzle disposed extending about and enclosing an outer periphery of the inner nozzle, a first inlet connecting with the inner nozzle, and a second inlet connecting with the outer nozzle;

a gases feed unit for feeding gases to the discharging device through the first inlet; and

a material feed unit for feeding a highly viscous material or a foamable material to the discharging device through the second inlet, the highly viscous material being fluid in the form of a stream in a high speed flow region and capable of retaining a shape into which it is molded in a low speed flow region.

18. A bead molding apparatus for molding foamed bead comprising:



US 4,360,000

a discharging device including an inner nozzle disposed extending at a tip portion, an outer nozzle disposed extending about and enclosing an outer periphery of the inner nozzle, a first inlet connecting with the inner nozzle, and a second inlet connecting with the outer nozzle;

a foamable material feed unit for feeding a foamable material to the discharging device through the first inlet; and

a material feed unit for feeding a highly viscous material to the discharging device through the second inlet, the highly viscous material being fluid in the form of a stream in a high speed flow region and capable of retaining a shape into which it is molded in a low speed flow region.

19. The bead molding apparatus as claimed in claim 18, wherein the foamable material feed unit feeds a mixture of the gases with the highly viscous material as the foamable material.

20. The bead molding apparatus as claimed in claim 19, wherein the foamable material feed unit comprises:

a plurality of piston pumps arranged so as to perform an suction stroke and a extrusion stroke by reciprocally moving a piston in a cylinder;

a gases injection unit for supplying gases under a predetermined pressure into the cylinder; and

a formable material supplying unit for a pump control unit for controlling the plurality of the piston pumps in such a manner that each of the plurality of the piston

pumps is arranged to conduct the suction stroke for feeding gases and with the highly viscous material after the suction stroke and to conduct the extrusion stroke for discharging the mixture of the gases with the highly viscous material as the foamable material as well as that a time difference is provided for the extrusion stroke of each of the plurality of the piston pumps so as to continually discharge a predetermined quantity of the foamable material.

21. The bead molding apparatus as claimed in claim 20, wherein the foamable material feed unit further comprises a tubular path for dispersing minute bubbles of gases disposed in a discharge path of each piston pump.

22. The bead molding apparatus as claimed in ~~any one of~~ claims 17 [to 21], wherein the discharging device is arranged so as for each of the inner nozzle and the outer nozzle to change an inner dimension of its inner wall into a smaller size over a region extending from an end portion of connection with a body of the discharging device to a tip portion thereof having a defined inner dimension.

23. The bead molding apparatus as claimed in ~~any one of~~ claims 17 [to 22], wherein an outer wall portion of each of the inner nozzle and the outer nozzle containing an edge section at the top thereof has an inclining surface joining at an acute angle to the direction of the flow of the highly viscous material stream or the foamable material stream.

24. The bead molding apparatus as claimed in ~~any one of~~

0361433-050901

claims/ 17 [to 23], wherein the inner nozzle and the outer nozzle are provided, respectively, with a first control valve for controlling the opening and closing of a path reaching the inner nozzle from the first inlet and a second control valve for controlling the opening and closing of a path reaching the outer nozzle from the second inlet.

25. The bead molding apparatus as claimed in claim 24, wherein the discharging device is capable of being hand-carried; and each of the first control valve and the second control valve is capable of being opened and closed by a manual on-off operation.

26. The bead molding apparatus as claimed in claim 24, wherein each of the first control valve and the second control valve is capable of being opened and closed automatically in response to an control signal.

27. The bead molding apparatus as claimed in claim 26, further comprising:

a manipulator mounted on the discharging device at a top portion thereof and disposed so as to be movable to a desired position in response to a control signal; and

a control unit for automatically controlling the movement of the manipulator and the discharging of the discharging device in accordance with a predetermined program.

28. The bead molding apparatus as claimed in claim 27, wherein the control unit automatically controls the movement of the manipulator and the discharge of the discharging device so as to automatically apply and mold

the hollow bead or the foamed bead on a applying position of each of a plurality of work being carried on a manufacturing line one after another.

29. The bead molding apparatus as claimed in claim 28, further comprising a detection unit for detecting an actual applying position of work the bead by the discharging device;

wherein the control unit controls the manipulator so as to bring the actual applying position detected thereby substantially into agreement with a predetermined target applying position of work.

30. The bead molding apparatus as claimed in claim 29, further comprising an image pick-up unit for picking up an image of the bead applied and molded on the applying position,

wherein the control unit automatically decides to determine whether the bead is applied and applied thereon in a favorable fashion by comparing the image of the bead picked-up by the image pick-up unit with a pre-stored reference image of the bead applied and molded in a favorable fashion.

31. A bead molding method for molding a hollow bead from a hot melt material that is fluid in the form of a stream in a middle-high temperature region and can retain a shape into which the hollow bead are molded in a middle-low temperature region;

a gas stream forming step for forming a gas stream flowing in a one direction;

a material stream forming step for forming a hot melt material stream in the middle-high temperature region within an outer peripheral space about and outside so as to enclose the gas stream; and

a bead molding step for molding the hollow bead into an irregular shape by lowering the middle-high temperature of the hot melt material to the middle-low temperature while fluidizing the hot melt material flowing in the outer peripheral space about the gas stream.

32. A bead molding method for molding a hollow bead from a foamable hot melt material for forming a foamed body, comprising:

a gases stream forming step for forming a gas stream in a one direction;

a material stream forming step for forming a stream of the foamable hot melt material in the direction identical to the direction of the gas stream within an outer peripheral space about and enclosing the flow of the gas stream; and

a bead molding step for molding the hollow bead into an irregular shape by foaming the foamable hot melt material flowing within the outer peripheral space of the gas stream.

33. The bead molding method as claimed in claim 31 [or 32], wherein the bead molding step molds the hollow bead into a shape corresponding to and following the shape of a applying position by transferring the hot melt material stream or the foamable hot melt material stream along the

applying position while applying the work with the hot melt material or the foamable hot melt material.

34. The bead molding method as claimed in claim 33, wherein:

there is disposed a discharging device including an inner nozzle elongated at a tip portion thereof and an outer nozzle elongated about and enclosing an outer periphery of the inner nozzle;

the gases stream forming step forms the gas stream in a one direction by discharging gases from the inner nozzle;

the material stream forming step forms the hot melt material stream or the foamable hot melt material stream in the same direction as the gas stream by discharging the hot melt material or the foamable hot melt material from the outer nozzle; and

the bead molding step forms the hollow bead into the shape corresponding to and following the shape of the applying position by transferring the hot melt material stream or the foamable hot melt material stream along a predetermined locus while discharging the gas stream from the inner nozzle and the material stream from the outer nozzle toward the work.

35. A bead molding method for molding a foamed bead comprised of a foamed body covered with a hot melt material that is fluid in the form of a stream in a middle-high temperature region and can retain the shape into which it is molded in a middle-low temperature region; comprising:

a foamable stream forming step for forming a stream

of a foamable hot melt material for forming the foamed body;

a material stream forming step for forming a stream of the hot melt material flowing in the middle-high temperature region within an outer peripheral space the foamable hot melt material stream about and enclosing the foamable hot melt material stream; and

a bead-molding step for molding the foamed bead into an irregular shape by reducing the middle-high temperature region to the middle-low temperature region while fluidizing the hot melt material stream flowing within the outer peripheral side outside and about the foamable hot melt material stream.

36. The bead molding method as claimed in claim 35, wherein the bead-molding step molds the foamed bead into a shape corresponding to and following the shape of the applying position by transferring the foamable hot melt material stream and the hot melt material stream along the applying position while applying the work with the foamable hot melt material and the hot melt material.

37. The bead molding method as claimed in claim 35 [or 36], wherein:

there is disposed a discharging device including an inner nozzle elongated at a tip portion thereof and an outer nozzle elongated enclosing an outer periphery of the inner nozzle;

the foamable material stream forming step forms the foamable hot melt material stream in the one direction by

discharging the foamable hot melt material from the inner nozzle; and

the material stream forming step forms the hot melt material stream in the direction equal to the direction of the foamable hot melt material stream and enclosing the foamable hot melt material by discharging the hot melt material from the outer nozzle.

38. The bead molding method as claimed in claim 36, wherein:

there is disposed a discharging device including an inner nozzle elongated at a tip portion thereof and an outer nozzle elongated enclosing an outer periphery of the inner nozzle;

the foamable material stream forming step forms the foamable hot melt material stream in the one direction by discharging the foamable hot melt material from the inner nozzle;

the material stream forming step forms the hot melt material stream in the same direction as the direction of the foamable hot melt material stream and enclosing the formable not melt material by discharging the hot melt material from the outer nozzle; and

the bead molding step for molding a foamed bead into a shape corresponding to and following the shape of the applying position by transferring the material stream along a given position while discharging the foamable hot melt material and the hot melt material from the inner nozzle and the outer nozzle, respectively.



39. The bead molding method as claimed in claim 37 [or 38], wherein:

the discharging device is mounted on a manipulator disposed to be movable to a desired position in response to a control signal; and

the bead molding step applies and molds the hollow bead or the foamed bead automatically on the applying position of a plurality of work members being carried on a manufacturing line one after another by controlling the movement of the discharging device by means of the manipulator.

40. A bead forming apparatus for forming a hollow bead comprising:

a discharging device including an inner nozzle elongated at a tip portion thereof, an outer nozzle elongated about and enclosing an outer periphery of the inner nozzle, a first inlet connecting with the inner nozzle, and a second inlet connecting with the outer nozzle;

a gases feed unit for feeding gases to the discharging device through the first inlet; and

a material feed unit for feeding a hot melt material or a foamable hot melt material to the discharging device through the second inlet, the hot melt material being fluid in the form of a stream in a middle-high temperature region and can retain the shape into which the material is molded in a middle-low temperature region.

41. A bead forming apparatus for forming a foamed bead

comprising:

a discharging device including an inner nozzle elongated at a tip portion thereof, an outer nozzle elongated about and enclosing an outer periphery of the inner nozzle, a first inlet connecting with the inner nozzle, and a second inlet connecting with the outer nozzle;

a first material feed unit for feeding a foamable hot melt material to the discharging device through the first inlet; and

a second material feed unit for feeding a hot melt material to the discharging device through the second inlet, the hot melt material being fluid in the form of a stream in a middle-high temperature region and can retain the shape into which the material is molded in a middle-low temperature region.

42. The bead molding apparatus as claimed in claim 41, wherein the first material feed unit feeds a mixture of the gases with the hot melt material as the foamable hot melt material.